

Fomax F9104NF Panel PC



◆ Specifications

Model		Fomax F9104NF
Basic Configuration		
CPU	Onboard Intel® Atom™ D2550 1.86GHz, 1M Cache, 64 Bit, Dual-Core	
Chipset	Intel® NM10	
Memory	2GB DDR3 SODIMM (1×SODIMM), Max. 4GB	
Storage	1×500GB, With 24×7 operation (Standard) HDD (2.5"), SSD, mSATA (Option)	
Expansion Slots	1×PCI, 1×Mini-PCIe (full-size, share with mSATA)	
I/O Interface	Standard: 1×RS-232/422/485, 4×RS-232 (rear); 2×RS-232 (Internal, optional external) Standard: 4×USB 2.0 (rear); 4×USB 2.0 (Internal, optional external) 2×SATA 2.0, 1×mSATA 2×10/100/1000M 1×VGA, 1×DVI-D 1×Line in, 1×Line Out, 1×Mic 1×PS/2 Keyboard, 1×PS/2 Mouse Power Switch, Power LED, Power Interface	
Video Memory	On board, DVMT	
Drivers		
Option	External USB DVD-ROM or DVD-RW	
Monitoring		
Watchdog	0~255 Sec	
Displays		
Type	19" SXGA TFT LCD	
Resolution	1280×1024	
Brightness	250cd/m ²	
Contrast Ratio	1000:1	
Viewing Angle	170° (H), 160° (V)	
Backlight	LED	
Touchscreen	5-wire resistive type (Standard)	
Power		
Power Input	12VDC Input (3 Port terminal), with 100~240VAC power adapter	
Mechanical Specifications		
Cooling	Fanless	
Construction	Aluminum Front Panel & Stainless Steel Panel, VESA	
Mounting		
Dimensions (W×H×D)	464mm×375mm×90mm	
Cutout Size (W×H)	403mm×331mm	
Weight	8.6kg (w/o power adapter)	
Environmental		
Operating Temperature	0~50°C	
Storage Temperature	-0~70°C	
Relative Humidity	10~85% (non-condensing)	
IP Rating	IP65 compliant front panel	
Certification	FCC, CE	



Shanghai Nematron Technology Co., Ltd.

245 Xinjun Ring Road, Suite D302 Caohejing Pujiang Hi-Tech Park, Shanghai 201114, China

Tel: +86 21 5109 6600

Fax: +86 21 5426 3008