

LP1700 Industrial Monitor



◆ Specifications

Model		LP1700
Displays		
Type	17" SXGA TFT LCD	
Resolution	1280 × 1024	
Pixel pitch	0.264mm × 0.264mm	
Luminance	250cd/m ²	
Contrast ratio	1000:1	
Response time	5ms	
Display color	16.7M	
Viewing angle	170°(H), 160°(V)	
LCD life time	30,000 hrs	
OSD Control	Support (front)	
Touchscreen (Option, LP1700T)		
Type	5-wire, Analog resistive	
Transparency	80±2%	
Knock test	35,000,000 times	
Touchscreen port	USB or RS-232	
Display		
Display Interface	1 × VGA, 1 × DVI-I	
Power		
Input	12VDC (Standard, with power adapter)	
	18~36VDC (Option, without power adapter)	
Power adapter	Input: 100~240VAC, 50~60Hz Output: 12VDC / 5A	

KVM Switch (Option, LP1700T-KVMP)	
Connections	2 (connect 2 computer)
K&M interface	USB
Cable length	1.8m
Mechanical	
Construction	Aluminum front panel & Stainless Steel
Panel Color	Cold Grey (Standard)
Mounting	Panel mount, Rack mount, VESA (75 / 100mm)
Dimension (W×H×D)	483mm × 355mm × 57mm
Cutout Size (W×H)	428mm × 318mm
Weight	7kg
Environmental	
Operating Temperature	0~50°C
Storage Temperature	-20~60°C
Relative Humidity	10~90% (non-condensing)
Altitude	10,000ft
Vibration	1g, 5~500Hz
Shock	15g
IP Rating	IP65, NEMA 4/4X/12 compliant front panel
Certification	FCC, CE



Shanghai Nematron Technology Co., Ltd.

245 Xinjun Ring Road, Suite D302 Caohejing Pujiang Hi-Tech Park, Shanghai 201114, China

Tel: +86 21 5109 6600

Fax: +86 21 5426 3008