

Smart T6x08 Series Emedded IPC



◆ Specifications

Model	Smart T6008	Smart T6108	Smart T6208	Smart T6308
CPU				
Default Configuration	Onboard 6th/7th Intel® Core™ i5, 64 Bit, Dual-Core, BGA1356			
Memory				
Default Configuration	4GB DDR4 SODIMM (2×SODIMM) Max. 32GB			
Slots				
PCI or PCIe	None	1×PCI (Standard); 1×PCI-Ex4 (Option)	2×PCI (Standard); 1×PCI-Ex4, 1×PCI-Ex1 (Option)	3×PCI
Mini-PCIe	1×full-size			
Storage				
Default Configuration	1×500GB (With 24×7 operation)			
Option	CFast, HDD (2.5"), SSD, mSATA			
I/O Interface				
Serial Port	2×RS-232/485 (COM1/2: rear), 2×RS-232/422/485 (COM3/4: rear), 2×RS-232 (COM5/6: front)			
Parallel Port	1 (rear)			
USB	2×USB 2.0 (rear), 4×USB 3.0 (2 front, 2 rear)			
SATA	1×SATA 2.0 (7+15Pin), 1×mSATA, 1×CFast			
LAN	2×10/100/1000M			
GPIO	16-Bit			
Audio	1×Line-Out, 1×Mic			
K&M Port	1×PS/2 Keyboard, 1×PS/2 Mouse			
Display				
Video Port	1×VGA, 1×HDMI			
Video Memory	On board, DVMT			
Monitoring				
Watchdog	0~255 Sec			

Power			
Default Configuration	100~240VAC, 1.6A, 50/60Hz; 12VDC, 7.5A (power adapter) DC-in: 12~24VDC		
Mechanical Specifications			
Cooling	Fanless		
Construction	Aluminum & Steel		
Mounting	Desktop, Wallmount		
Dimensions (W×H×D)	246mm×63mm×209mm	246mm×93mm×209mm	246mm×132mm×209mm
Environmental			
Operating Temperature	-20~60°C (with wide temperature storage)		
Storage Temperature	-40~80°C		
Relative Humidity	5~95% (non-condensing)		
Certification	CE, FCC		



Shanghai Nematron Technology Co., Ltd.

245 Xinjun Ring Road, Suite D302 Caohejing Pujiang Hi-Tech Park, Shanghai 201114, China

Tel: +86 21 5109 6600

Fax: +86 21 5426 3008